

Liniar 70mm PVCu Casement Window System

Beautifully engineered and brilliantly functional, the PVCu window system, manufactured in-house using advanced Liniar profile, delivers leading performance with U-values as low as 0.93 W/m²K and a range of high security and weatherproofing features.

Available in a wide variety of configurations, the PVCu window system can be designed to complement traditional and contemporary architecture. For added customisation, a broad selection of colours and finishes and glass options are available.

DESIGN FEATURES

- Achieves energy rating of A
- Tested to PAS24
- Double rebated seal for greater energy efficiency
- Patented bubble gasket seal to eliminate draughts and leaks
- A clean, sleek appearance with no visible gaskets
- Sculptured and chamfered finishes available

OPTIONS

- Glazing 28mm or 36mm
- Side hung, top hung, tilt and turn, run through sash horns and bay configurations available
- Range of customisable hardware
- Woodgrain foiled colour options available
- Available in single and dual colour options
- Available for new build or refurbishment projects
- Hinge protectors offered



SPECIFICATIONS

Performance and accreditations

U-value (Double Glazing):	1.2 W/m ² K
U-value (Triple Glazing):	0.93 W/m ² K
Window Energy Rating (WER):	A
Acoustic Performance:	32 (-1: -5) dB
Security:	PAS24
Part Q security compliance:	✓

System

Depth:	70mm
--------	------

Configurations

Opening	Open-Out
Top Hung	✓
Side Hung	✓
Bottom Hung	—
Tilt & Turn	✓
Fixed Light	✓
Multi-Light	✓
French Casement	✓
Run Through Sash Horns	✓

Glazing

Glazing Thickness:	28mm or 36mm
--------------------	--------------

System Features

Single Colour:	✓
Dual Colour:	✓
Hardware:	Fab&Fix as standard
Multi Point Locking:	✓

